3LACC GX









HONDA GX270

HONDA









APPLICATIONS



Domestic Cleaning



Tradesmen



Commercial Cleaners



Agriculturist





STANDOUT FEATURES



AAA™ Comet™ **Italian made** triplex plunger pump delivers performance & reliability.



Industrial Honda[™] GX270 pull start series engine.



Jetwave Safety System™ (JSS) thermal and safety valve to prevent overheating in excessive bypass and over pressurisation.




13" premium pneumatic tyres.



0°, 15, 25, 40 and snap-on nozzles.



Dual M22 screw hose coupling system.













TECHNICAL DATA 0:00

BLACK GX

Product Code

Pressure / Flow Rate 4000 PSI (275 BAR) / 13.5 L/PM (810 L/PH) / 3.5 GPM

Max Inlet Temp 60°C / 140°F

Class (AS/NZS: 4223) A (3,712 Bar/Litres)

Usage Frequency Semi Professional: Weekly

Nozzle Size

Frame Structure Heavy duty steel black powder coat 2-wheel trolley

MOTOR FEATURES

Engine / Power Honda™ GX270 Pull Start (air cooled) 9HP / 270cc

Fuel Type / Capacity / Protection Unleaded / 4.5L / Low Oil Shutdown

عيلير **HYDRAULIC FEATURES**

Pump / Head / Pistons Plunger Triplex / Brass / Ceramic

Motor Pump Coupling / Pump RPM Direct Drive / 3400RPM

Unloader Valve Integral

Safety Valve Yes

Detergent Injector Yes - Downstream low pressure (with powerboost technology)

DIMENSIONS & WEIGHT

 $940mm(L) \times 560mm(W) \times 680mm(H) / 66KG$ Machine Dimensions / Weight

WARRANTY(S) 🕢

Unit / Pump Warranty* 1 Year Engine Warranty* 📆 🔜 3 Years

OPTIONAL ACCESSORIES

10m Extension Hose + M22 Joiner JWA018-EX JW3 Foaming Lance with Tank JWA221

Copyright © 2024 Jetwave® Group Pty Ltd. All Rights Reserved.

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement. *Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).







